AD-A092 182 PURDUE UNIV LAFAYETTE IN SCHOOL OF ELECTRICAL ENGINEERING F/G 9/2
PASM: A RECONFIGURABLE MULTIMICROCOMPUTER SYSTEM FOR IMAGE PROC--ETC(U)
APR 80 H J SIEGEL AFOSR-78-3581

UNCLASSIFIED AFOSR-TR-80-1087 NL

1 of 1
AD A

END
DATE FILMED
1-81
DTIC


1.0
1.1
1.25
1.4
1.6
1.8
2.0
2.2
2.5
2.8
3.2
3.6
4.0
MICROCOPY RESOLUTION TEST CHART

AD A092182

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS BEFORE COMPLETING FORM

1. REPORT NUMBER: AFOSR-TR-80-1087	2. GOVT ACCESSION NO.: AD-A092182
3. RECIPIENT'S CATALOG NUMBER	
4. TITLE (and Subtitle): PASM: A RECONFIGURABLE MULTIMICROCOMPUTER SYSTEM FOR IMAGE PROCESSING.	5. TYPE OF REPORT & PERIOD COVERED: Interim rept.
	6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s): Howard Jay Siegel	8. CONTRACT OR GRANT NUMBER(s): AFOSR-78-3581
9. PERFORMING ORGANIZATION NAME AND ADDRESS: Purdue University, School of Electrical Engineering, West Lafayette, IN 47907	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS: 61102F 2304/A2
11. CONTROLLING OFFICE NAME AND ADDRESS: Air Force Office of Scientific Research/NM, Bolling AFB, Washington, DC 20332	12. REPORT DATE: April 1980
	13. NUMBER OF PAGES: 5
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report): UNCLASSIFIED
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

DTIC ELECTE NOV 28 1980 S D E

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

To be presented at the Workshop on NEW COMPUTER ARCHITECTURES and IMAGE PROCESSING Ischia, Italy, June 2-5, 1980

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

80 11 06 085

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

As a result of the microprocessor revolution, it is now feasible to build multimicroprocessor systems capable of performing image processing tasks more rapidly than previously possible. There are several types of parallel processing systems. An SIMD (single instruction stream/multiple date stream) machine typically consists of a set of N processors, N memories, an interconnection network, and a control unit (e.g. Illiac IV). The control unit broadcasts instructions to the processors and all active ("turned on") processors execute the same instruction at the same time. Each processor executes instructions using data teken from a

DDC FILE COPY

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

292000

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

20. Abstract continued.

memory with which only it is associated. The interconnection network allows interprocessor communication. An MSIMD (multiple-SIMD) systems is a parallel processing system which can be structured as two or more independent SIMD machines (e.g. MAP). An MIMD (multiple instruction stream/multiple data stream machine typically consists of N processors and N memories, where each processor can follow an independent instruction stream (e.g. C.mmp). As with SIMD architectures, there is a multiple data stream and an interconnection network. A partitionable SIMD/MIMD system is a parallel processing system which can be structures as two or more independent SIMD and/or MIMD machines. In this presentation, PASM, a partionable SIMD/MIMD system being designed at Purdue University for image processing and pattern recognition, is described.

Accession For
NTIS GRA&I
DDC TAB
Unannounced
Justification
By
Distribution/
Availability Codes
Dist | Avail and/or special
A

AFOSR-TR- 80 - 1087

PASM: A RECONFIGURABLE MULTIMICROCOMPUTER SYSTEM FOR IMAGE PROCESSING

Howard Jay Siegel

Purdue University
School of Electrical Engineering
West Lafayette, IN 47907, USA

April 1980

To be presented at the
Workshop on
New Computer Architectures and Image Processing
Ischia, Italy
June 2-5, 1980

80 11 06 085

This research was supported by the Air Force Office of Scientific Research, Air Force Systems Command, USAF, under Grant No. AFOSR-78-3581.

Approved for public release;
distribution unlimited.

AIR FORCE OFFICE OF SCIENTIFIC RESEARCH (AFSC)
NOTICE OF TRANSMITTAL TO DDC
This technical report has been reviewed and is
approved for public release IAW AFR 190-12 (7b).
Distribution is unlimited.
A. D. BLOSE
Technical Information Officer

As a result of the microprocessor revolution, it is now feasible to build multimicroprocessor systems capable of performing image processing tasks more rapidly than previously possible. There are several types of parallel processing systems. An SIMD (single instruction stream - multiple data stream) machine typically consists of a set of N processors, N memories, an interconnection network, and a control unit (e.g. Illiac IV). The control unit broadcasts instructions to the processors and all active ("turned on") processors execute the same instruction at the same time. Each processor executes instructions using data taken from a memory with which only it is associated. The interconnection network allows interprocessor communication. An MSIMD (multiple-SIMD) system is a parallel processing system which can be structured as two or more independent SIMD machines (e.g. MAP). An MIMD (multiple instruction stream - multiple data stream) machine typically consists of N processors and N memories, where each processor can follow an independent instruction stream (e.g. C.mmp). As with SIMD architectures, there is a multiple data stream and an interconnection network. A partitionable SIMD/MIMD system is a parallel processing system which can be structured as two or more independent SIMD and/or MIMD machines. In this presentation, PASM, a partitionable SIMD/MIMD system being designed at Purdue University for image processing and pattern recognition, is described.

SIMD machines can be used for "local" processing of segments of images in parallel. For example, the image can be segmented, and each processor assigned a segment. Then, following the same set of instructions, such tasks as line thinning, threshold dependent operations, and gap filling can be done in parallel for all segments of the image simultaneously. Also in SIMD mode, matrix arithmetic used for such tasks as statistical pattern recognition can be done efficiently. MIMD machines can be used to perform

different "global" pattern recognition tasks in parallel, using multiple copies of the image or one or more shared copies. For example, in cases where the goal is to locate two or more distinct objects in an image, each object can be assigned a processor or set of processors to search for it. An SIMD/MIMD application might involve using the same set of microprocessors for preprocessing an image in SIMD mode and then doing a pattern recognition task in MIMD mode.

PASM is a large-scale dynamically reconfigurable multimicroprocessor system. It is a special purpose system being designed to exploit the parallelism of image processing and pattern recognition tasks.

Due to the low cost of microprocessors, computer system designers have been considering various multimicrocomputer architectures. PASM combines the following features:

(1) it can be partitioned to operate as many independent SIMD and/or MIMD machines of varying sizes, and

(2) a variety of problems in image processing and pattern recognition will be used to guide the design choices.

Figure 1 is a block diagram of the basic components of PASM. The Parallel Computation Unit (PCU) contains $N = 2^n$ processors, N memory modules, and an interconnection network. The PCU processors are microprogrammable microprocessors that perform the actual SIMD and MIMD computations. The PCU memory modules are used by the PCU processors for data storage in SIMD mode and both data and instruction storage in MIMD mode. The interconnection network provides a means of communication among the PCU processors and memory modules.

The Micro Controllers (MCs) are a set of microprogrammable microprocessors which act as the control units for the PCU processors in SIMD mode and

orchestrate the activities of the PCU processors in MIMD mode. There are Q = 2^q MCs. Each MC controls N/Q PCU processors. A virtual SIMD machine (partition) of size RN/Q where R = 2^r and $1 \leq r \leq q$, is obtained by loading R MC memory modules with the same instructions simultaneously. Similarly, a virtual MIMD machine of size RN/Q is obtained by combining the efforts of the PCU processors of R MCs. Q is therefore the maximum number of partitions allowable, and N/Q is the size of the smallest partition. Possible values for N and Q are 1024 and 16, respectively. Control Storage contains the programs for the MCs.

The Memory Management System controls the loading and unloading of the PCU memory modules. It employs a set of cooperating dedicated microprocessors. The Memory Storage System stores these files. Multiple devices are used to allow parallel data transfers.

The System Control Unit is a conventional machine, such as a PDP-11, and is responsible for the overall coordination of the activities of the other components of PASM. By carefully choosing which tasks should be assigned to the System Control Unit and which should be assigned to other system components (such as the Memory Management System), the System Control Unit can work effectively and not become a bottleneck.

In a companion presentation, examples of image processing on PASM type systems are discussed. The improvement in execution time, over that on a uniprocessor system, is examined for various tasks.



Fig. 1. Block diagram overview of PASM.